

Item	Parameter
Description	A-frame
Uses	Finding cable isolation faults to ground and for pipe line coating defects
Construction	Carbon fiber reinforced glass fiber construction
Weight	4.0lbs (1.80kg)
Dimension	28.3in(L) x 25.2(W) x 1.6in(H) (720mm x 640mm x 40mm)
Features	<ul style="list-style-type: none"> - Lightweight construction - Ergonomic design (does not drag the ground when carrying)
Operating Frequency	3Hz/6Hz
Connection Cable	4 pin XLR connector/RVVP 4 x 0.12mm ² /300V/ 1.5m length
Compatible With Receivers	vLocPro, vLocDM, vLocML, vLocPro2, vLocDM2, vLocML2, vLoc-9800
Power Supply	Powered by receiver
External Connectors	1 x 4 pin connection socket-(XLR)
Approvals	CE/FCC
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)
Weather Proof	IP 54 and NEMA 4
Shipping Weight	9.9lbs (4.50kg)
Shipping Dimension	31.5in(L) x 27.8in(W) x 4.5in(H) (800mm x 705mm x 115mm)
Warranty	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.

<p>USA Vivax-Metrotech Corp. 3251 Olcott Street, Santa Clara, CA 95054, USA</p> <p>T/Free: +1-800-446-3392 Tel: +1-408-734-1400 Fax: +1-408-734-1415</p> <p>sales@vxmt.com www.vivax-metrotech.com</p>	<p>Canada Vivax Canada Inc. 400 Esna Park Drive, Unit 17, Markham, Ontario, L3R 3K2, Canada</p> <p>Tel: +1-289-846-3010 Fax: +1-905-752-0214</p> <p>CanadianSales@vxmt.com www.vivax-metrotech.com</p>	<p>Europe SebaKMT Seba Dynatronic Mess-und Ortungstechnik GmbH Dr.-Herbert-Iann-Str. 6, 96148 Baunach, Germany</p> <p>Tel: +49-9544-680 Fax: +49-9544-2273</p> <p>service@sebakmt.com www.sebakmt.com</p>	<p>Australasia SebaKMT AUS Unit 1, 176 South Creek Road, Cromer NSW 2009, Australia</p> <p>Tel: +61-2-9972-9244 Fax: +61-2-9972-9433</p> <p>sales@sebakmtaus.com service@sebakmtaus.com www.sebakmtaus.com</p>	<p>China Leidi Utility Supply (Shanghai) Ltd. Rm405 3rd Building No. 641, Tianshan Rd, Shanghai, China 200336</p> <p>Tel: +86-21-5187-3880 Fax: +86-21-5168-5880</p> <p>info@leidi.cn www.leidi.com</p>
--	--	--	--	---